

PICO RIVERA ATI DISTRIBUTION FACILITY ACQUIRED JANUARY 2022

ULBRICH OF CALIFORNIA

ALLOYS AND CAPABILITIES OVERVIEW

ALLOYS AVAILABLE

Stainless Steels: AM350, A286, 304, 316L, 321, 347, 444

Titanium: Titanium Grade 1, Titanium Grade 2

Nickel Based: Inconel® 600, Inconel® 625 and 625LCF, Inconel® 718, Hastelloy® C276, Hastelloy® X, Nickel 201

CERTIFICATIONS

AS9100D, ISO 9001:2015, Pratt-Whitney LCS

SLITTING CAPABILITIES

Light Gauge:

Thickness: .0005 – .008” (0.0127 – 0.2032 mm)

Widths: .068 – 12” (1.727 – 304.8 mm)

Standard Width Tolerance: +/- 0.003” (0.0762 mm)

Standard:

Thickness: .002 – .045” (0.0508 – 1.143 mm)

Widths: 0.500 – 24” (12.7 – 609.60 mm)

Standard Width Tolerance: +/- 0.005” (0.127mm)

HIGH-SPEED REWINDING

Thickness: .002 – .025” (0.0508 – 0.635mm)

Widths: 6 – 42” (152.4 – 1066.8mm)

Standard Width Tolerance: +/-0.50” (12.7mm)

PACKAGING

Standard Export Packaging

Specialized / Custom Packaging Available Upon Request

PRIMARY MARKETS AND APPLICATIONS SERVED

Aerospace: Heat Exchangers, Gaskets, Fasteners

Industrial/Electronics: Bellows for Semiconductor Manufacturing

Power Generation: Gaskets, High Pressure Seals

Alternative Energy/: Stack Components, Separator Sheets,
Hydrogen Fuel Cell Anode / Cathode Plates

SUPPLY CHAIN PARTNER

Flexible MOQs and Reduced Lead Times